

January
2008



Application

Large driveways can be secured with one barrier arm.



NEW PRODUCT INTRODUCTION

Michelangelo 19'8" & 26'3" Barriers



Benefits

- Unique design of top lid for easy access to the control board. The lid locks in the open position and allows you to work safely and comfortably.
- Cover a span of up to 26.3 feet with a single boom
- High speed stable operation of boom
- Continuous operation thermostatically controlled ventilation system
- No need for spring adjustments saves time
- Attractive design and color with durable paint
- Optional flashing lights available for the booms and the barrier body
- Round and rectangle booms available
- Telescopic boom available (16 foot base boom available for both 19' 8" and 26' 3" foot booms)
- Photocell aligned with boom

Technical Features

	Michelangelo 60	Michelangelo 80
Maximum driveway	19' 8" (6m)	26' 3" (8m)
Type	Electromechanical	Electromechanical
Power supply	120 volt	120 volt
Motor Power Supply	24 volt DC	24 volt DC
Current consumption	2.5 Amp.	2.5 Amp.
Power consumption	1/2hp (300W)	1/2hp (300W)
Torque	440 LbFt (600 Nm)	440 LbFt (600 Nm)
Opening/Closing Time	6 seconds	8 seconds
Service	100%	100%
Slow Down	Yes	Yes
Electronic Limit Switches	Yes	Yes
Anti-squashing	Yes	Yes
Boom Height From Floor	32" (800mm)	32" (800mm)

Pricing To be advised

For more information please contact us at:

T: 561 995 8155 • Toll free: US. 877 995 8155 • info.bft@bft-usa.com

www.bft-usa.com

BFT U.S., Inc.

6100 Broken Sound Pkwy N.W.,
Suite 14
Boca Raton, FL, 33487
USA