



9050 VEHICULAR SLIDE GATE OPERATOR

• RESIDENTIAL



- Electronic magnetic limits eliminate old style mechanical switches that can wear out, break or fail
- Automatic self-setting limits mean no limit switch adjustments – ever
- Safety – built-in mechanical and electronic reverse system
- Advanced microprocessor control board features programming switches to set the mode of operation required and has ports for DKS plug-in loop detectors to simplify wiring
- 5-year limited warranty



entrapment detection
reverses gate when obstructed



built in
power switch and reset switch



fail-safe release
never be locked out (or in)




unique design
allows easy access to all mechanical parts

9050 VEHICULAR SLIDE GATE OPERATOR

9050 1/2 HP

12" W x 24" H x 11.5" D (30.5cm W x 61cm H x 29.2cm D)



	CLASS OF OPERATION	MAX GATE LENGTH *	MAX GATE WEIGHT *	MOTOR	INPUT
9050 1/2 HP	I	16 Ft (4.9 m)	300 Lbs. (136 kg)	1/2HP Continuous Duty AC Motor	115 VAC, 60 HZ, 5.4A

* Assumes gate to be in good condition and swinging in a level plane.

Technical Features

Mechanical

Frame: G90 Galvanized steel to prevent rusting
 Cover: Steel cover is plated and painted
 Primary Reduction: Single cog belt
 Speed: Approximately 10 in/sec (254 mm/sec)
 Chain: Unit is shipped with 20-ft (6M) of #40 roller chain, chain brackets, hardware
 Fail-Safe release standard

Options

Nickel or stainless steel chain
 Base Plate for post mounting
 Fail-Secure release kit

Electrical

Automatic limit adjustment
 Auto-close timer 1-23 sec
 Selectable stop / reverse loop function
 Built in On / Off switch
 Built in alarm reset switch
 Two 115 VAC convenience outlets for accessory transformers
 Automatically assumes fail-safe mode when an entrapment condition exists
 Ports for plug-in open and reverse loop detectors.
 DKS plug-in detectors only

Miscellaneous

Environmental: 10°F to 140°F (-12°C to 62°C)
 Thermostatically controlled heater kit recommended for colder environments
 External entrapment/obstruction sensing devices must be used with this operator
 Shipping weight approximately 70 Lbs (31.8 kg)



Access Control Solutions since 1948

Distributed by:

MEMBER:



DOOR KING® INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A.
 Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com

© 2012 All Rights Reserved. Product specifications may change without notice.
 Rev. 9/12