

HEADQUARTERS

ITALY

FAAC spa
Via Calari 10 - 40069 Zola Predosa (BO)
Tel. +39 051 61724 - Fax +39 051 758518
info@faac.it - www.faac.it

FAAC SUBSIDIARIES

AUSTRALIA

FAAC AUSTRALIA PTY LTD
Homebush – Sydney, Australia
tel. +61 2 87565644
fax +61 2 87565677
www.faac.com.au

AUSTRIA

FAAC GE.S. M.B.H.
Wals – Siezenheim, Austria
tel. +43 662 8533950
fax +43 662 85339520
www.faac.at

BENELUX

FAAC BENELUX
Brugge, Belgium
tel. +32 50 320202
fax +32 50 320242
www.faacbenelux.com

CINA

FAAC SHANGHAI
Shanghai, Cina
tel. +86 21 68182970
fax +86 21 68182968
www.faac.com.cn

ESPAÑA

F.A.A.C. SA
Madrid, España
tel. +34 91 6613112
fax +34 91 6610050
www.faac.es

F.A.A.C. SA Delegación Cataluña
Barcelona, España
tel. +34 93 4362000
fax +34 93 4368225
www.faac.es

FRANCE

FAAC FRANCE
Corbas, France
tel. +33 4 72218700
fax +33 4 72218701
www.faac.fr

FAAC NORD S.A.S.
Massy, France
tel. +33 1 69191620
fax +33 1 69191621
www.faac.fr

GERMANY

FAAC GMBH
Freilassing, Germany
tel. +49 8654 49810
fax +49 8654 498125
www.faac.de

INDIA

FAAC INDIA PVT. LTD
Noida – Delhi, India
tel. +91 120 3934100/4199
fax +91 120 4212132
www.faacindia.com

MIDDLE EAST

FAAC MIDDLE EAST BRANCH
Dubai Airport Free Zone, UAE
tel. +971 42146733
fax +971 42146734
www.faac.ae

POLSKA

FAAC POLSKA SP.ZO.O
Warszawa, Polska
tel. +48 22 8141125
fax +48 22 8142024
www.faac.pl

SCANDINAVIA

FAAC SCANDINAVIA AB
Bankeryd, Sweden
tel. +46 36 376860
fax +46 36 370780
www.faac.se

SWITZERLAND

FAAC AG
Altdorf, Switzerland
tel. +41 41 8713440
fax +41 41 8713484
www.faac.ch

UNITED KINGDOM

FAAC UK LTD.
Basingstoke Hampshire, UK
tel. +44 1256 318100
fax +44 1256 318101
www.faac.co.uk

USA

FAAC INTERNATIONAL INC
Jacksonville, USA
tel. +1 904 448 8952
fax +1 904 448 8958
www.faacusa.com

Fullerton, USA
tel. +1 714 446 9800
fax +1 714 446 9898
www.faacusa.com



DSL2000 - DSW2000 24VDC Commercial Vehicular Gate Operators

FAAC



Headquarter & East Coast Operations
FAAC International Inc.
5151 Sunbeam Road
Suites 9-11
Jacksonville, Florida 32257
Tel. 866 925 3222 Toll Free
Tel. 904 448 8952
Fax 904 448 8958

West Coast Operations
FAAC International Inc.
357 South Acacia Avenue
Unit 357
Fullerton, California 92831
Tel. 800 221 8278 Toll Free
Tel. 714 446 9800
Fax 714 446 9898

PAD MOUNT SERIES

24V

FAAC

24VDC COMMERCIAL GATE OPERATORS: EASY INSTALLATION, FULL FEATURE, BUILT-IN BATTERY BACKUP SYSTEM

- Operates vehicular gates for high traffic and residential applications and is ideal for custom homes, apartments, self storage, and other commercial applications.
- Multi-Function battery backup is a standard feature built-in and offers main power fail and low battery control of the gate during a power failure.
- The 24VDC direct drive motor to gearbox design offers high power efficiency while reducing costs and added parts.
- Built in soft start soft stop control offers a smooth, more quiet operation and is easier on the gate and gate installation.
- Simple to install design offers multiple prewired terminals, LED indicators, installation handles, accessory shelves, and is easy to access and set limits.
- Wireless master slave is simple to install and eliminates the need for underground wire.

OPERATOR FEATURES

- Built-in battery backup standard
- Soft Start Soft Stop smooth operation
- Heavy duty gearbox and 24VDC motor direct drive design
- Simple, clean design with less moving parts
- Fail safe design with tamper detect feature on DSL2000 slide gate operator
- Release handle with optional padlock on DSW2000 swing gate operator
- Zinc galvanized steel frame with handles for easy installation
- DSW2000's claim shell cover can be removed without removing swing arm
- DSL2000 uses a UV protected polyethylene cover with lift handle slots
- Easy access limits are simple to set
- Battery & accessory shelves
- Adjustable chain idlers for front, rear, and post mount slide gates
- Industry standard swing arm for swing gate applications
- Plug-in loop detector inputs: reverse, open, center (shadow)
- (2) AC accessory power plugs
- Built-in 3-Button control for easy setup
- Multiple terminal inputs for simple, clean wire installation
- Maglock, solenoid, external alarm outputs
- Power fail option can open or cycle gate
- Low battery option can open or cycle gate
- Anti-Tailgate & Quick Close features standard
- Wireless master slave option



Wireless Master Slave Option



Built-in Battery Backup



Heavy duty gearbox with direct motor drive



Simple design with easy to set limits



DIMENSIONS AND TECHNICAL CHARACTERISTICS

General	
Power input	120 VAC, 15A
Motor	24 VDC
Power	500 W, 1/2 HP
Power input fuse	4 amp SLB
Accessory fuse	5 amp FB
AC accessory outlets	2
Accessory power output	24DC
M/S wire	RS432, CAT5 wire

DSL2000 Slide Gate Operator	
Gearbox	15:1 Fail Safe
Chain Size	#41, 25ft
Chain height - front mount	11" from base
Chain mount options	Front, rear, center
Travel speed	12 inches/sec
Gate capacity	1000 lbs, 40 feet
Shipping weight	125 lbs
Dimensions	22" H, 18" W, 15" D

DSW2000 Swing Gate Operator	
Gearbox	900:1 Fail Secure
Arm type	Industry standard
Arm attachment height	17" from base
Mounting method	Pad or baseplate
Travel speed	90 degrees in 15 sec
Gate capacity	800 lbs, 18 feet
Shipping weight	150 lbs
Dimensions	18" H, 18.5" W, 23.5" D