

HEADQUARTERS

ITALY  
FAAC SpA  
Via Calari 10 - 40069 Zola Predosa (BO)  
Tel. +39 051 61724 - Fax +39 051 758518  
info@faac.it - www.faac.it

SUBSIDIARIES

<p>AUSTRALIA</p> <p>FAAC AUSTRALIA PTY LTD Homebush – Sydney, Australia tel. +61 2 87565644 fax +61 2 87565677 www.faac.com.au</p>	<p>GERMANY</p> <p>FAAC GMBH Freilassing, Germany tel. +49 8654 49810 fax +49 8654 498125 www.faac.de</p>	<p>SPAIN</p> <p>F.A.A.C. SA Alcobendas - Madrid, Spain tel. +34 91 6613112 fax +34 91 6610050 www.faac.es</p>
<p>AUSTRIA</p> <p>FAAC GMBH Salzburg, Austria tel. +43 662 8533950 fax +43 662 85339525 www.faac.at</p>	<p>INDIA</p> <p>FAAC INDIA PVT. LTD Noida – Delhi, India tel. +91 120 3934100/4199 fax +91 120 4212132 www.faacindia.com</p>	<p>SWITZERLAND</p> <p>FAAC AG Altdorf, Switzerland tel. +41 41 8713440 fax + 41 41 8713484 www.faac.ch</p>
<p>BENELUX</p> <p>FAAC BENELUX NV/SA Brugge, Belgium tel. +32 50 320202 fax +32 50 320242 www.faacbenelux.com</p>	<p>MIDDLE EAST</p> <p>FAAC MIDDLE EAST BRANCH Dubai Airport Free Zone - Dubai, UAE tel. +971 42146733 fax +971 42146734 www.faac.ae</p>	<p>UNITED KINGDOM</p> <p>FAAC UK LTD. Basingstoke - Hampshire, UK tel. +44 1256 318100 fax +44 1256 318101 www.faac.co.uk</p>
<p>CHINA</p> <p>FAAC SHANGHAI Shanghai, China tel. +86 21 68182970 fax +86 21 68182968 www.faacgroup.cn</p>	<p>POLAND</p> <p>FAAC POLSKA SP.ZO.O Warszawa, Poland tel. +48 22 8141422 fax +48 22 8142024 www.faac.pl</p>	<p>U.S.A.</p> <p>FAAC INTERNATIONAL INC Jacksonville, FL - U.S.A. tel. +1 904 4488952 fax +1 904 4488958 www.faacusa.com</p>
<p>FRANCE</p> <p>FAAC FRANCE Corbas - Lyon, France tel. +33 4 72218700 fax +33 4 72218701 www.faac.fr</p> <p>FAAC FRANCE - AGENCE PARIS Massy - Paris, France tel. +33 1 69191620 fax +33 1 69191621 www.faac.fr</p>	<p>NORDIC REGIONS</p> <p>FAAC NORDIC AB BOX 125, SE-284 22 Perstorp, Sweden tel. +46 435 779500 fax +46 435 779529 www.faac.se</p>	<p>FAAC INTERNATIONAL INC Fullerton, California - U.S.A. tel. +1 714 446 9800 fax +1 714 446 9898 www.faacusa.com</p>



Headquater & East Coast Operations  
FAAC International Inc.  
5151 Sunbeam Road  
Suites 9-11  
Jacksonville, Florida 32257  
Tel. 866 925 3222 Toll Free  
Tel. 904 448 8952  
Fax 904 448 8958

West Coast Operations  
FAAC International Inc.  
357 South Acacia Avenue  
Unit 357  
Fullerton, California 92831  
Tel. 800 221 8278 Toll Free  
Tel. 714 446 9800  
Fax 714 446 9898

Rev. 1.0 - 12/2010



DSL2000 - DSW2000  
24VDC Commercial Vehicular Gate Operators



24VDC COMMERCIAL GATE OPERATORS:  
EASY INSTALLATION, FULL FEATURE,  
BUILT-IN BATTERY BACKUP SYSTEM


- Operates vehicular gates for high traffic and residential applications and is ideal for custom homes, apartments, self storage, and other commercial applications.
- Multi-Function battery backup is a standard feature built-in and offers main power fail and low battery control of the gate during a power failure.
- The 24VDC direct drive motor to gearbox design offers high power efficiency while reducing costs and added parts.
- Built in soft start soft stop control offers a smooth, more quiet operation and is easier on the gate and gate installation.
- Simple to install design offers multiple prewired terminals, LED indicators, installation handles, accessory shelves, and is easy to access and set limits.
- Wireless master slave is simple to install and eliminates the need for underground wire.

OPERATOR FEATURES

- Built-in battery backup standard
- Soft Start Soft Stop smooth operation
- Heavy duty gearbox and 24VDC motor direct drive design
- Simple, clean design with less moving parts
- Fail safe design with tamper detect feature on DSL2000 slide gate operator
- Release handle with optional padlock on DSW2000 swing gate operator
- Zinc galvanized steel frame with handles for easy installation
- DSW2000's claim shell cover can be removed without removing swing arm
- DSL2000 uses a UV protected polyethelene cover with lift handle slots
- Easy access limits are simple to set
- Battery & accessory shelves
- Adjustable chain idlers for front, rear, and post mount slide gates
- Industry standard swing arm for swing gate applications
- Plug-in loop detector inputs: reverse, open, center (shadow)
- (2) AC accessory power plugs
- Built-in 3-Button control for easy setup
- Multiple terminal inputs for simple, clean wire installation
- Maglock, solenoid, external alarm outputs
- Power fail option can open or cycle gate
- Low battery option can open or cycle gate
- Anti-Tailgate & Quick Close features standard
- Wireless master slave option



Wireless Master Slave Option



Built-in Battery Backup



Heavy duty gearbox with direct motor drive



Simple design with easy to set limits



DIMENSIONS AND TECHNICAL CHARACTERISTICS

General	
Power input	120 VAC, 15A
Motor	24 VDC
Power	500 W, 1/2 HP
Power input fuse	4 amp SLB
Accessory fuse	5 amp FB
AC accessory outlets	2
Accessory power output	24DC
M/S wire	RS432, CAT5 wire

DSL2000 Slide Gate Operator	
Gearbox	15:1 Fail Safe
Chain Size	#41, 25ft
Chain height - front mount	11" from base
Chain mount options	Front, rear, center
Travel speed	12 inches/sec
Gate capacity	1000 lbs, 40 feet
Shipping weight	125 lbs
Dimensions	22" H, 18" W, 15" D

DSW2000 Swing Gate Operator	
Gearbox	900:1 Fail Secure
Arm type	Industry standard
Arm attachment height	17" from base
Mounting method	Pad or baseplate
Travel speed	90 degrees in 15 sec
Gate capacity	800 lbs, 18 feet
Shipping weight	150 lbs
Dimensions	18" H, 18.5" W, 23.5" D