

VMD AC/DC

For low Voltage, Battery & Solar Applications

Applications

- Safety detects moving vehicles in an industrial environment where there are blind areas along the driving path and actuates warning lights.
- Energy Conservation detects vehicles along a driving path and turns light on only in the proximity of the moving vehicle.
- Security detects approaching vehicles or an unauthorized movement of a parked vehicle and actuates alarms, video cameras or annunciator.
- Access Control (free exit) vehicle detector for gates, overhead doors and parking barriers.
- Driveway Annunciator may be tied to the doorbell announcing the approach of a vehicle entering the driveway

VMD



EMX Industries, Inc.

4564 Johnston Parkway, Cleveland, Ohio 44128

P. 800 426 9912 F. 216 518 9884


Sales Inquiries: salesupport@emxinc.com **Technical Support:** technical@emxinc.com
www.emxinc.com

Indicators & Controls

- The VMD draws 4 mA current in standby mode to help lower power needs for solar applications
- Easier integration into security control panels or gate and door operators with the small 3.0" x 0.9" x 2.75" housing.
- All controls mounted on the front panel of the unit providing for easy access and operation.
- The VMD operates on 9 – 24 VDC or 24 VAC
- May be wired stand-alone using the included LD-7P terminal block
- May be installed on the EMX ULTRA II-MB by simply plugging it in and hooking up a probe



Probe-XX
(Probe XX= lead wire length)



HAR-12-2
(Harness for ULTRA II-MB)



LD-7P
Plug in terminal block for VMD or ULTRA II

Technical Data

Range sensitivity	15 ft. diameter around probe (7.5 ft. radius)
Sensitivity Adjustment	Dependent on mass and speed
Output on Time Adjustment	0.5...6 seconds 0.15 lbs. (68g)
Surge Protection	Probe input circuitry protected by surge suppressors
Relay Output Configuration	Form C (SPDT)
Relay Contact Rating	1A @ 24VDC, 1A @ 120VAC
Detect Indicator	Red LED
Power Indicator	Green LED
Power	9...24VDC or 24VAC (do not exceed 35V _{peak})
Standby Current	4mA
Detection Current	50mA
Operating Temperature	-40°C...82°C (-40°F...180°F) 0...95% relative humidity
VMD™ Housing Material	ABS (plastic)
VMD™ Dimensions (L x W x H)	3.0"(76mm) x 0.9"(22mm) x 2.75"(70mm)
VMD™ Weight	0.15 lbs. (68 g)
Probe Housing Material	PVC water-tight
Probe Dimensions (L x Dia.)	17" (432mm) x 1" (25mm)
Probe Cable	3-wire, shielded, direct burial

Ordering Information

- VMD AC/DC 9-24 VDC 24 VAC
- LD-7P 7 Accessory control add on board
- ULTRA II-MB Accessory control add on board
- 130-10020316 ULTRA II MB mounting plate
- HAR-12-2 12 Pin Harness with 2 feet wire
- Probe-XX XX = Lead length (example Probe-50 = 50 foot lead)

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of sale to our customer. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship. Rev 2.1 11/24/09